

**MOTOCOOL EXP -37°C**

**Motorbike ready to use cooling liquid**  
**Anti-corrosion and anti-freeze, Protection -37°C/-35°F**  
**Nitrite free / Amine free / Phosphate free**

**TYPE OF USE**

MOTUL Motocool Expert is a ready to use cooling liquid, anti-freeze and anti-corrosion for bikes cooling systems. Based on monoethyleneglycol, Motocool Expert contains reinforced hybrid anti-corrosion additives suitable for light aluminum alloys used in bike engine design.

**PERFORMANCES**

Protects the cooling system from freezing (-37°C / -35°F) and metallic parts from corrosion.  
Provides an excellent thermal exchange to improve engine cooling efficiency.  
Avoid engine overheating with its high boiling point: 135°C / 275°F (at +1.5 bar).  
Outstanding anti-corrosion and anti-cavitation properties that remain while aging.  
Seals, rubber pipes and plastic parts friendly.  
Anti-foam properties.  
Contains a bitter-tasting agent to prevent from ingesting: coolants and antifreezes have a sweet taste but are harmful if swallowed.

**RECOMMENDATIONS**

Ready to use, do not add any water.  
Drain intervals: Refer to the manufacturers' recommendation.  
This product should not be used to protect drinking water systems against freezing.  
STORAGE: Avoid light exposure during storage.

**PROPERTIES**

Color	Visual	Yellow
Density at 20°C (68°F)	ASTM D4052	1.075
pH	ASTM D1287	7.9

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



## MOTOCOOL EXP -37°C

**Motorbike ready to use cooling liquid**  
**Anti-corrosion and anti-freeze, Protection -37°C/-35°F**  
**Nitrite free / Amine free / Phosphate free**

Freezing point	ASTM D1177	-37.0 °C / -35.0 °F
Alkalinity reserve	ASTM D1121	8.0 mg KOH/g
Boiling point		135.0 (+1.5 bar) °C / 275.0 (+1.5 bar) °F



## MOTOCOOL EXP -37°C

**Motorbike ready to use cooling liquid**  
**Anti-corrosion and anti-freeze, Protection -37°C/-35°F**  
**Nitrite free / Amine free / Phosphate free**

STANDARDS	
AFNOR	1506431772034
ASTM STANDARD	1517504516350
BRITISH STANDARD	1515087885658
JAPANESE STANDARD	1517503929739, 1515406544620, 1517503929739
SAE	1506431804237